**Product Specifications** 





# **FEATURES**

- For use with potable water, distribution systems and hydronic heating systems
- Material: Lead Free Brass (metal alloy C46500)
- Maximum Temperature: 180° F
- Maximum Pressure: 100 psi
- Made of DZR (dezincification resistant) lead free forged brass
- Can be used for potable water, distribution systems and hydronic heating systems
- Can be used with Copper crimp rings and Stainless clamps (sold separately)
- Complies with ASTM F1807 standards
- Compatible with PEX pipe ASTM F876-877 standards



TEES					
Model #	Size	Α	В	С	
MLPXBT121212	1/2	1.929	0.965	0.965	
MLPXBT343434	3/4	2.165	1.083	1.083	
MLPXBT111	1	2.756	1.378	1.378	
MLPXBT121234	1/2 x 1/2 x 3/4	2.047	0.984	1.024	
MLPXBT34341	3/4 x 3/4 x 1	2.441	1.236	1.220	
MLPXBT343412	3/4 x 3/4 x 1/2	1.929	1.063	0.965	
MLPXBT341234	3/4 x 1/2 x 3/4	2.126	1.063	1.063	
MLPXBT341212	3/4 x 1/2 x 1/2	2.028	1.083	0.965	
MLPXBT1134	1 x 1 x 3/4	2.520	1.201	1.260	
MLPXBT1112	1 x 1 x 1/2	2.362	1.201	1.181	
MLPXBT1341	1 x 3/4 x 1	2.579	1.378	1.201	
MLPXBT13434	1 x 3/4 x 3/4	2.343	1.201	1.083	
MLPXBT13412	1 x 3/4 x 1/2	2.185	1.201	1.024	
MLPXBT1121	1 x 1/2 x 1	2.579	1.378	1.201	
MLPXBT383838	3/8 x 3/8 x 3/8	1.929	0.965	0.965	













### Warranty


See warranty information for more details.














COUPLINGS					
Model #	Size	Α	В	C	
MLPXBC12	1/2	1.398	0.543	0.138	
MLPXBC34	3/4	1.398	0.780	0.138	
MLPXBC1	1	1.752	0.976	0.138	
MLPXBC3412	1/2 x 1/2 x 3/4	1.949	1.173	0.157	
MLPXBC134	3/4 x 3/4 x 1	2.126	1.173	0.157	
MLPXBC1238	3/4 x 3/4 x 1/2	1.398	0.425	0.138	
MLPXBC38	3/4 x 1/2 x 3/4	1.398	0.425	0.138	
MLPXBTCKIT1	1	1.744	1.043	0.130	



SWIVEL AD	DAPTER(BRAS	S NUT)	
Model #	Size	Α	В
MLPXBFSWABN12	1/2	1.437	NPSM ½"
MLPXBFSWABN34	3/4	1.437	NPSM ¾"
MLPXBFSWABN1234	1/2 x 3/4	1.437	NPSM ¾"
SWIVEL AD	APTER(PLAST	IC NUT)	
Model #	Size	Α	В
MLPXBFSWAPN12	1/2	1.535	NPSM ½"



ELBOW					
Model #	Size	Α	В	C	D
MLPXBL12	1/2	1.201	1.201	1.024	0.965
MLPXBL34	3/4	1.398	1.398	1.063	1.063
MLPXBL1	1	1.811	1.811	1.378	1.378
MLPXBL3412	3/4 x 1/2	1.260	1.201	1.024	0.965
MLPXBL38	3/8"	1.201	1.201	0.965	0.965



DROP-EAR ELBOW				
Model #	Size	Α	В	С
MLPXBFDEL12	1/2	1.260	1.142	NPT ½"
MLPXBFDEL34	3/4	1.260	1.260	NPT ¾"
MLPXBFDEL3412	3/4 x 1/2	1.280	1.417	NPT ¾"


# Warranty

See warranty information for more details.



# **Product Specifications**







SWEAT FEMALE ELBOW				
Model #	Size	Α	В	С
MLPXBFSL12	1/2	1.043	0.807	0.626
MLPXBFSL34	3/4	1.181	1.142	0.878
MLPXBFSL1234	1/2 x 3/4	1.181	1.094	0.878

COPPER CRIMP RING				
Model #	Size	OD	L	Т
MLPXPCR1	1	16	8.25	1.47
MLPXPCR12	1/2	19.05	8.25	1.42
MLPXPCR34	3/4	25.4	8.25	1.42
MLPXPCR38	3/8	31.75	9.27	1.24

SWEAT FEMALE ELBOW				
Model #	Size	Α	В	С
MLPXBMSL34	3/4	1.122	1.417	0.874





MALE ELBOW				
Model #	Size	Α	В	С
MLPXBML12	1/2	1.181	0.984	NPT ½"
MLPXBML34	3/4	1.220	1.181	NPT ¾"

PLUGS				
Model #	Size	Α	В	C
MLPXBP12	1/2	0.768	0.543	0.138
MLPXBP34	3/4	0.768	0.780	0.138
MLPXBP1	1	0.945	0.976	0.138


# Warranty

See warranty information for more details.



**Product Specifications** 







FEMLE ADAPTER				
Model #	Size	Α	В	С
MLPXBFA12	1/2	1.260	1.102	NPT ½"
MLPXBFA34	3/4	1.280	1.378	NPT ¾"
MLPXBFA1	1	1.654	1.654	NPT 1"
MLPXBFA1234	1/2 x 3/4	1.280	1.378	NPT ¾"
MLPXBFA3412	3/4 x 1/2	1.280	1.083	NPT ½"
MLPXBFA341	3/4 x 1	1.476	1.654	FPT 1"

ی		_ 🕿
	A	

MALE ADAPTER					
Model #	Size	Α	В	С	
MLPXBMA12	1/2	1.319	0.984	NPT ½"	
MLPXBMA34	3/4	1.339	1.181	NPT ¾"	
MLPXBMA1	1	1.693	1.496	NPT 1"	
MLPXBMA1234	1/2 x 3/4	1.339	1.181	NPT ¾"	
MLPXBMA3412	3/4 x 1/2	1.319	1.063	NPT ½"	
MLPXBMA341	3/4 x 1	1.516	1.299	NPT ¾"	
MLPXBMA134	1 x 3/4	1.516	1.299	NPT ¾"	



SWEAT FEMALE ADAPTER						
Model #	Size	Α	В			
MLPXBFSA12	1/2	1.220	0.626			
MLPXBFSA34	3/4	1.496	0.878			
MLPXBFSA1	1	1.831	1.130			
MLPXBFSA3412	3/4 x 1/2	2.087	1.380			



SWEAT MALE ADAPTER					
Model #	Α	В			
MLPXBMSA12	1/2	1.260	0.626		
MLPXBMSA34	3/4	1.575	0.874		
MLPXBMSA1	1	1.850	1.126		
MLPXBMSA3412	3/4 x 1/2	1.260	0.626		

	C
<b>a</b>	PP PB
	A

SWIVEL ADAPTER(BRASS NUT)					
Model #	Size	Α	В	С	
MLPXBTCKIT12	1/2	1.378	0.543	0.138	
MLPXBTCKIT34	3/4	1.378	0.827	0.138	


# Warranty

See warranty information for more details.




# **Product Specifications**





SWIVEL ELBOW(BRASS NUT)					
Model # Size A B C					
MLPXBFSLBN12	1/2	1.152	0.984	NPSM ½"	



SWIVEL ELBOW(PLASTIC NUT)					
Model # Size A B C					
MLPXBFSLPN12	1/2	1.152	1.087	NPSM ½"	



COPPER ELBOW				
Model #	Size	Α	В	С
MLPXBS128	3 ½" X 8"	7.803	3.189	/
MLPXBS126	½" X 6"	5.677	3.189	/
MLPXBFSO126	½" X 6"	5.677	3.189	/
MLPXBFSO128	½" X 8"	7.803	3.189	/

#### Performance:

100 psi / 689 kPa Max. pressure 180 °F / 82 °C (water) Max. temperature

Potable water, distribution systems Water

& hydronic heating systems

Above or underground (protected)

Interior installation With or without an access panel Exterior installation

Metal alloy:

C46500 DZR (Dezincification resistant)

### Complies with:

**ASTM F1807** CSA B137.5 ANSI/NSF Standard 61 ANSI/NSF Standard 372 ANSI/NSF Standard 14

#### Compatible with PEX pipe:

ASTM F876-877

### Warranty

See warranty information for more details.







