# For Commercial & Residential Applications

Job Name	Contractor
Job Location	Approval
Engineer	Contractor's P.O. No.
Approval	Representative

# **Series WGV-X**

## **Brass Cross-Handle Gate Valves**

Sizes 3/8" - 3" (10 - 80mm)

Series WGV-X Brass Cross-Handle Gate Valves are ideal for general service on water, oil or compressed gas applications. This Series features threaded bonnet, non-rising stem, solid wedge disc and brass body.

#### **Features**

- Threaded bonnet
- Non-rising stem
- Solid wedge disc
- Brass body
- $\bullet$  %" 3" (10 80mm) threaded end connections

#### Pressure - Temperature

• 200psi (13.8 bar) WOG non-shock to 180°F (82°C)




### **Specifications**

Valve shall be manufactured out of brass and be pressure rated to 200psi WOG non-shock. Valve shall have threaded bonnet, non-rising stem and solid wedge disc. Valve shall be a Watts Series WGV-X.

## Dimensions — Weight

WEIGHT	
kg	
.23	
.26	
.37	
.53	
.75	
.97	
1.50	
2.92	
3.90	
1	



#### NOTICE

The information contained herein is not intended to replace the full product installation and safety information available or the experience of a trained product installer. You are required to thoroughly read all installation instructions and product safety information before beginning the installation of this product.

Watts product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Watts Technical Service. Watts reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Watts products previously or subsequently sold.

WATTS

**USA:** T: (978) 689-6066 • F: (978) 975-8350 • Watts.com **Canada:** T: (905) 332-4090 • F: (905) 332-7068 • Watts.ca **Latin America:** T: (52) 81-1001-8600 • Watts.com

ES-WGV-X 0621 © 2006 Watts